



Marine & Offshore

Certificate number: 05611/I0 BV File number: ACM 135/2014/001

Product code: 2103l

This certificate is not valid when presented without the full attached schedule composed of 7 sections

www.veristar.com

# TYPE APPROVAL CERTIFICATE

This certificate is issued to

## AMNITEC LIMITED

Merthyr Tydfil - UNITED KINGDOM

for the type of product

# METALLIC HOSES (FLEXIBLE PIPES) ASSEMBLIES

Metallic flexible hoses in stainless steel covered with stainless steel braid

## Requirements:

- BUREAU VERITAS Rules for the Classification of Steel Ships
- BUREAU VERITAS Rules for the Classification of Offshore Units

This certificate is issued to attest that Bureau Veritas Marine & Offshore did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.

This certificate will expire on: 18 Sep 2028

For Bureau Veritas Marine & Offshore,

At BV LONDON, on 18 Sep 2023, Spencer Yule

This certificate was created electronically and is valid without signature



This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

Certificate number: 05611/I0 BV

# THE SCHEDULE OF APPROVAL

#### 1. PRODUCT DESCRIPTION

Metallic flexible hoses in stainless steel covered with stainless steel braid

1.1 Maximum working pressure (bar)

Single braided	Double braided
167	220
136	210
100	178
74	103
70	125
65	86
50	76
39	57
35	55
30	44
26	46
22	40
20.6	27
21.5	34
	167 136 100 74 70 65 50 39 35 30 26 22 20.6

Max Design Temperature: 550°C

### 1.2 Material specification

1	
UFBX corrugated hose	BS EN 10088-2:2005 grades 1.4404 or 1.4541
Braid	BS EN 10088-3:2005 grades 1.4401 or 1.4541
Fittings	Stainless Steel 304, 321 or 316

When other choices of materials are used per manufacturer's recommendations, the BV agreement is to be obtained.

### 2. DOCUMENTS AND DRAWINGS

- Manufacturer's catalogue dated 2023

No departure from the above documents shall be made without the prior consent of the Society. The manufacturer must inform the Society of any modification or changes to these documents and drawings.

### 3. TEST REPORTS

- Test report N°F(QR) 91.001 dated 14/03/2018 including the burst test, pressure and elongation tests
- Pliability test report dated 2022

# 4. APPLICATION / LIMITATION

- 4.1 May be used for the following services on board:
- Liquid fuel, heated liquid fuel, lubrication oil, steam, fresh and sea water, compressed air, exhaust gas
- 4.2 Material of fittings and flanges shall comply with the relevant requirements of Bureau Veritas Rules.
- 4.3 Taper threaded fittings are not to be used for liquid fuel pipings and oil pipings located in engine room and in spaces containing a source of ignition.
- 4.4 Temperature reduction factors are to be taken into account for maximum working pressure caused by temperature influence according to manufacturer's specifications.
- 4.5 The hoses are to be limited to a length necessary to provide for relative movement between fixed and flexibly mounted items of machine/equipment or systems. When the hoses are intended to be used for essential services or containing either flammable or toxic media, they are not to exceed 1.5 m in length. The hoses are to be installed in clearly visible and readily accessible locations at all times.
- 4.6 The use of stainless steel is to be restricted as per the requirements of the Bureau Veritas Rules.
- 4.7 The hoses are to be installed according to manufacturer's instructions and Bureau Veritas Rules and Regulations stated on the front page of this certificate.

Certificate number: 05611/I0 BV

#### **5. PRODUCTION SURVEY REQUIREMENTS**

- 5.1 The products are to be supplied by **AMNITEC LIMITED** in compliance with the type and the requirements described in this certificate.
- 5.2 This type of product is within the category IBV of Bureau Veritas Rule Note NR320.
- 5.3 BV product certificate is required.
- 5.4 Each metallic flexible pipe with end fittings is to be hydraulically pressure tested to 1,5 the maximum working pressure and provided with the manufacturer's pressure test report and conformity of production.
- 5.5 For information, **AMNITEC LIMITED** has declared to Bureau Veritas the following production site:

AMNITEC LIMITED: Abercanaid, Merthyr Tydfil, Mid. Glamorgan, UNITED KINGDOM

#### 6. MARKING OF PRODUCT

Each hose is to be at least permanently marked with:

- Manufacturer name or logo
- Type designation
- Date of manufacture
- Nominal Diameter
- Pressure Rating
- Temperature Rating
- Society's brand as relevant

#### 7. OTHERS

It is **AMNITEC LIMITED**'s responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.

This certificate supersedes the Type Approval Certificate N° 05611/H0 BV issued by the Society.

\*\*\* END OF CERTIFICATE \*\*\*